

DOWNLIGHT

ZEF DOWNLIGHT-21W-4000K-IP20

BL02212005

INDOOR > Downlight (100 to 240 mm)

Economic downlight, with low luminance effect. Ideal for circulations, toilets, waiting room...

**Application domain**

- Circulations areas
- Cloakrooms
- Washrooms



21 W

2260
lmIRC
>80

IP20

4000K

F

Electric data

Total power (W)	21
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
Light source type	-
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2260lm (4000K)
ULOR	-

Technical data

Diameter (mm)	242
Height (mm)	106
Recessed diameter (mm)	Min. : 200 Max. : 220
Weight (kg)	0.58
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK04
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Isolant rouleau

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	100°
Tiltable	No

Other

