

PROJECTOR

POWER FLOODLIGHT 3CCT-100-150-200W

BL102006510

OUTDOOR > Outdoor Flood Light

High power projector with color and power temperature change.
Adapt the lighting in situ according to the customer's needs.
Master the desired effect once installed.



Application domain

- Industrial facilities
- Production areas, assembly plant
- School
- Outdoor illumination
- Outdoor lighting



FILE UPDATED ON 04/04/2023

Electric data

Total power (W)	200
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 6500K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>70
Safety group (EN62778)	RG1
Luminous flux (lm)	28000lm (4000K)
ULOR	-



FILE UPDATED ON 04/04/2023



Technical data

Dimensions (mm)	56 x 394 x 376
Weight (kg)	5.4
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Black
IK Code	IK06
Incandescent wire test	850°C
IP Code	IP65
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	Verre trempé
Driver included	Yes
Recoverable	Non concerné

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	150° X 100°
Tiltable	No
Connection type	Fil à connecter



FILE UPDATED ON 04/04/2023





FILE UPDATED ON 04/04/2023