

SLIM ECO

TF069-SLIM ECO-12W-IP20-4000k-NON GRAD

BL02122001

INDOOR > Downlight (100 to 240 mm)

Economic flat downlight with direct opal diffuser 230 Volts. Corner LED wall light 110



Electric data

Total power (W)	12
Rated voltage (V)	230V
Distorsion harmonique	<20%
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No



FILE UPDATED ON 26/04/2023

Power supply data

Max. lamp per B10A circuit breaker	15
Max. lamp per B16A circuit breaker	20
Max. lamp per C16A circuit breaker	30

Photometric data

Color temperatures	4000K
UGR	<22
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>6
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	990lm (4000K)
ULOR	-



FILE UPDATED ON 26/04/2023



Technical data

Diameter (mm)	168
Height (mm)	24
Recessed diameter (mm)	Min. : 155 Max. : 160
Weight (kg)	0.22
Recessed depth under BA13 (mm)	200
Cable length	30 cm
Product color	White
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +40°
Body material	PC
Diffuser material	PS
Driver included	Yes

Liefe time

L70 à 25°	25 000 h
-----------	----------

Supplementary data

Warranty period	2 years
Light beam spread	110°
Tiltable	No
Connection type	Connecteur rapide avec repiquage



FILE UPDATED ON 26/04/2023





FILE UPDATED ON 26/04/2023