





TF140-TUBE ECOPLUS 150-60W-4000K-IP65

BL11606601

INDOOR > Surface mounted and suspended fixtures
INDOOR > Triproof

Waterproof Tube with PC opal diffuser, stainless steel end cap. Crossing.



Application domain

- Industrial facilities
- Parkings lots and underground passages
- Storage







IRC >80

IP66





Electric data

Total power (W)	60
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	I
Dimmable	No

FILE UPDATED ON 21/04/2023

TOPLED NORDIC BE-LED. ALL RIGHTS RESERVED.



Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	6800lm (4000K)
ULOR	

Technical data

Dimensions (mm)	1510 x 82.5 x 82.5
Weight (kg)	1.88
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-25 +45°
Body material	PC - STAINLESS STEEL 304
Diffuser material	PC
Driver included	Yes
Recoverable	Non concerné



Liefe time

L70 à 25°	50 000 h

Supplementary data

Warranty period	3 years
Light beam spread	120°
Tiltable	Yes (360°)
Connection type	fast connector

Other

