

FOG

TF091-FOG-14W-IP66-WHITE-3000K-850°

BL12146502

INDOOR > Indoor Bulkhead

OUTDOOR > Outdoor Wall Light

OUTDOOR > Outdoor Bulkhead

Indoor or outdoor use, IP66, available with detector. Ideal for communities, garages and stairwells



Application domain

- Parkings lots and underground passages
- Circulations areas
- Stairs
- Outdoor Circulations



14 W

1200
lm

IRC
>80

IP66

3000K

F



FILE UPDATED ON 21/11/2022

Electric data

Total power (W)	14
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1200lm (3000K)
ULOR	-



FILE UPDATED ON 21/11/2022



Technical data

Diameter (mm)	300
Height (mm)	93.5
Recessed diameter (mm)	-
Weight (kg)	0.88
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-20... +50°
Body material	PC
Diffuser material	PC
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	110°
Tiltable	No
Connection type	Fast connect



FILE UPDATED ON 21/11/2022



Atmosphere



PROTECTED BY

Other



Other



FILE UPDATED ON 21/11/2022