

## CONSTRUCTION SPOTLIGHT

# FLOODLIGHT CHANTIER-30W-BATTERIE

BL10306502

### WORKSITE > Floodlight

Site projector to accompany your work. Compact and resistant, it is supplied with a 230 V charger. 3 possible lighting modes: 25%, 50% and 100%. 3 to 6 hours of battery use. USB port for charging a phone.



### Application domain

- Garages
- Production areas, assembly plant



30 W

4500  
lm

IRC  
>70

IP54

6000K

### Electric data

Total power (W)	30
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	III
Dimmable	No

## Photometric data

Color temperatures	6000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>6
IRC	>70
Safety group (EN62778)	RG1
Luminous flux (lm)	4500lm (6000K)
ULOR	-

## Technical data

Dimensions (mm)	88 x 269 x 211
Weight (kg)	1.7
Recessed depth under BA13 (mm)	-
Cable length	0
Product color	Black
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP54
Use temperature range	-20... +40°
Body material	Aluminium - PC
Diffuser material	PC
Driver included	Yes

## Liefe time

L70 à 25°	30 000 h
-----------	----------

## Supplementary data

Warranty period	2 years
Light beam spread	120°
Tiltable	No
Linked products	<ul style="list-style-type: none"><li>• PL10506511 - TRIPOD FOR CONSTRUCTION PROJ.</li></ul>

## Other

---

