

LED SPOTLIGHT

# SPOT LED LOW GLARE.5W-3CCT-IP54-30°- DIM-BL

BL01055401

**INDOOR** > Downlights (until 95 mm)

Small diameter, low luminance white LED spotlight. Ideal for specific enhancement or decoration.



## Application domain

- Residential indoor
- Kitchen
- Bedroom
- House Corridor



5 W

350 lm

UGR  
<19

IRC  
>80

IP54  
facade

3 CCT

3000K / 4000K  
5700K



FILE UPDATED ON 25/11/2022

## Electric data

Total power (W)	5
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

## Photometric data

Color temperatures	3000K / 4000K / 5700K
UGR	<19
Light source type	COB
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	350lm (4000K)
ULOR	-



FILE UPDATED ON 25/11/2022



## Technical data

Diameter (mm)	48
Height (mm)	58
Recessed diameter (mm)	Min. : 40   Max. : 40
Weight (kg)	0.18
Recessed depth under BA13 (mm)	48
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP54 facade
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	30°
Tiltable	No
Connection type	Connector on the product



FILE UPDATED ON 25/11/2022



## Atmosphere



## Atmosphere



CW

NW

WW



## Other



FILE UPDATED ON 25/11/2022