

LINE

LINE 11W-3000K-36°-DIM-BL

BL02112001

INDOOR > Downlights (until 95 mm)**INDOOR** > Downlight (100 to 240 mm)

Low luminance white square led downlight. Very contemporary and architectural, it is triac dimmable. 11w UGR<19 LED ceiling light, architectural recessed, dimmable triac, low glare, appreciated by decorators for its contemporary design.

**Application domain**

- Residential indoor
- Bedroom
- Home Office
- House Corridor
- Entrance Halls
- Shop



11 W

600 lm

UGR
<19IRC
>90

IP40

3000K

F



FILE UPDATED ON 15/02/2023

Electric data

Total power (W)	11
Rated voltage (V)	230V
Distorsion harmonique	<28%
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

Power supply data

Max. lamp per B10A circuit breaker	50
Max. lamp per B16A circuit breaker	60
Max. lamp per C16A circuit breaker	70

Photometric data

Color temperatures	3000K
UGR	<19
Light source type	-
SDCM	SDCM>4
IRC	>90
Safety group (EN62778)	RG1
Luminous flux (lm)	600lm (3000K)
ULOR	-



FILE UPDATED ON 15/02/2023



Technical data

Dimensions (mm)	75 x 75 x 51
Recessed diameter (mm)	Min. : 67 Max. : 67
Weight (kg)	0.28
Recessed depth under BA13 (mm)	60
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP40
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	36°
Tiltable	No
Connection type	Connector on the product



FILE UPDATED ON 15/02/2023

