

PROJECTOR

POWER FLOODLIGHT 3CCT-200-300-400W

BL104006510

OUTDOOR > Outdoor Flood Light

High power projector with color and power temperature change.
Adapt the lighting in situ according to the customer's needs.
Master the desired effect once installed.



Application domain

- Industrial facilities
- Production areas, assembly plant
- School
- Outdoor illumination
- Outdoor lighting



Electric data

| | |
|-----------------------|-------|
| Total power (W) | 400 |
| Rated voltage (V) | 230V |
| Distorsion harmonique | - |
| Power factor | >0.95 |
| Network frequencies | 50Hz |
| Electric class | I |
| Dimmable | No |

Photometric data

| | |
|----------------------------|-----------------------|
| Color temperatures | 3000K / 4000K / 6500K |
| Light source type | SMD |
| Including the light source | Yes |
| SDCM | SDCM>5 |
| IRC | >70 |
| Safety group (EN62778) | RG1 |
| Luminous flux (lm) | 64000lm (4000K) |
| ULOR | - |

Technical data

| | |
|--------------------------------|----------------|
| Dimensions (mm) | 65 x 545 x 447 |
| Weight (kg) | 10.2 |
| Recessed depth under BA13 (mm) | - |
| Cable length | - |
| Product color | Black |
| IK Code | IK06 |
| Incandescent wire test | 850°C |
| IP Code | IP65 |
| Use temperature range | -25... +45° |
| Body material | Aluminium |
| Diffuser material | Verre trempé |
| Driver included | Yes |
| Recoverable | Non concerné |

Liefe time

| | |
|-----------|----------|
| L80 à 25° | 50 000 h |
|-----------|----------|

Supplementary data

| | |
|-------------------|-----------------|
| Warranty period | 5 years |
| Light beam spread | 150° X 100° |
| Tiltable | No |
| Connection type | Fil à connecter |

