

APPLIED

UP&DOWN-APPLIQUE-3CCT-IP20-DIM- WHITE

BL12082001

INDOOR > Wall light

3CCT wall lamp. Ideal for hallways and walls. Direct and indirect lighting.



Application domain

- Residential indoor
- Meeting room
- Bedroom
- Home Office
- House Corridor
- Circulations areas



7.5 W

740 lm

IRC
>85

IP20

3 CCT

3000K / 4000K
5700K

E

Electric data

Total power (W)	7.5
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	I
Dimmable	Triac

Photometric data

Color temperatures	3000K / 4000K / 5700K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>85
Safety group (EN62778)	RG0
Luminous flux (lm)	740lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	67 x 242 x 77
Weight (kg)	0.62
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK04
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-25... +45°
Body material	PC
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	No
Connection type	Connecteur rapide avec repiquage

Atmosphere



Other

