

RECESSED SPOTLIGHT

# SPOT LED ENC.13W-3000K-60°-BL

BL01132001

**INDOOR** > Downlights (until 95 mm)

**INDOOR** > Downlight (100 to 240 mm)

Recessed spotlight 1000lm ideal for ceiling heights greater than 2.5m. &quot;Halogen&quot; type lens with recoil for low glare.



## Application domain

- Residential indoor
- Meeting room
- Bedroom
- Home Office
- Circulations areas



13 W

1000  
lm

IRC  
>80

IP40

3000K

D



FILE UPDATED ON 13/04/2023

## Electric data

|                       |      |
|-----------------------|------|
| Total power (W)       | 13   |
| Rated voltage (V)     | 230V |
| Distorsion harmonique | -    |
| Power factor          | >0.9 |
| Network frequencies   | 50Hz |
| Electric class        | II   |
| Dimmable              | No   |

## Photometric data

|                        |                |
|------------------------|----------------|
| Color temperatures     | 3000K          |
| Light source type      | -              |
| SDCM                   | SDCM>5         |
| IRC                    | >80            |
| Safety group (EN62778) | RG1            |
| Luminous flux (lm)     | 1000lm (3000K) |
| ULOR                   | -              |



FILE UPDATED ON 13/04/2023



## Technical data

|                                |                       |
|--------------------------------|-----------------------|
| Diameter (mm)                  | 85                    |
| Height (mm)                    | 89                    |
| Recessed diameter (mm)         | Min. : 68   Max. : 74 |
| Weight (kg)                    | 0.28                  |
| Recessed depth under BA13 (mm) | 79                    |
| Cable length                   | -                     |
| Product color                  | White                 |
| IK Code                        | IK06                  |
| Incandescent wire test         | 650°C                 |
| IP Code                        | IP40                  |
| Use temperature range          | -20... +45°           |
| Body material                  | Aluminium             |
| Diffuser material              | PC                    |
| Driver included                | Yes                   |
| Recoverable                    | Non recouvrable       |

## Liefe time

|           |          |
|-----------|----------|
| L70 à 25° | 50 000 h |
|-----------|----------|

## Supplementary data

|                   |         |
|-------------------|---------|
| Warranty period   | 5 years |
| Light beam spread | 60°     |
| Tiltable          | No      |



FILE UPDATED ON 13/04/2023

