

LED PANEL

TF064-PANEL 600x600-48W-4000k-IP65 FACADE

BL04486502

INDOOR > Office Recessed Fixture

Led panel IP65 facade 4800lm, ideal for kitchens, technical rooms, certain laboratories where the contribution of light will be very important



Application domain

- Medical areas
- Washrooms



FILE UPDATED ON 25/04/2023

Electric data

Total power (W)	48
Rated voltage (V)	230V
Distorsion harmonique	<20%
Power factor	>0.95
Network frequencies	50Hz
Electric class	II
Dimmable	No

Power supply data

Max. lamp per B10A circuit breaker	15
Max. lamp per B16A circuit breaker	20
Max. lamp per C16A circuit breaker	25

Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	4800lm (4000K)
ULOR	-



FILE UPDATED ON 25/04/2023



Technical data

Dimensions (mm)	595 x 595 x 10
Weight (kg)	2.72
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP65 facade
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC - PS
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none">• BL08000013 - TF066-Protrusion frame 600x600• BL08000002 - TF018 Mechanically welded projection frame• PL09302003 - DALI PUSH DIM POWER SUPPLY• BL08000009 - INTEGRATION FRAME 600x600



FILE UPDATED ON 25/04/2023





FILE UPDATED ON 25/04/2023

