

## LED PORTHOLE

# FOG 360-3000K-IP66

BL12256505

**INDOOR** > Indoor Bulkhead

**OUTDOOR** > Outdoor Bulkhead

Led porthole with external quick connector. IK10 and IP66



### Application domain

- School
- Outdoor residential
- Home Cellar, House Technical Room
- Cloakrooms
- Stairs
- Outdoor Circulations



24 W

2300  
lm

IRC  
>83

IP66

3000K

F



FILE UPDATED ON 07/04/2023

## Electric data

Total power (W)	24
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>83
Safety group (EN62778)	RG0
Luminous flux (lm)	2300lm (3000K)
ULOR	-



FILE UPDATED ON 07/04/2023

## Technical data

Diameter (mm)	310
Height (mm)	115
Recessed diameter (mm)	-
Weight (kg)	1.06
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	-
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-25... +45°
Body material	PC
Diffuser material	PC
Driver included	No
Recoverable	Non concerné

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	No
Connection type	fast connector



FILE UPDATED ON 07/04/2023





FILE UPDATED ON 07/04/2023

