

# PURE SMART 2 40W-UGR19-600X600-DETEC TR04402006

**INDOOR** > Office Recessed Fixture

LED panel in aluminum and polycarbonate. Autonomous luminaire with integrated HF presence detection and daylight management. 10 pre-programmed light levels.



## Application domain

- School



40 W	3900 lm	IRC >80	IP20	4000K
------	---------	---------	------	-------

## Electric data

Total power (W)	40
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3900lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	595 x 595 x 9
Weight (kg)	2.52
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	-
Driver included	No

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Light beam spread	120°
Tiltable	No
Connection type	Connecteur rapide avec repiquage

## Other

