

LED PANEL

PANEL BACKLIT PRO 675x675-36W-4000K- BL-PRISM

BL04362006

INDOOR > Office Recessed Fixture

Led panel UGR<19 with prismatic diffuser, with safety rope and connection terminal block that can be transplanted without tools, LGP in PMMA guaranteed for 5 years. Led panel UGR<19 with prismatic diffuser, with safety rope and connection terminal block that can be transplanted without tools, LGP in PMMA guaranteed for 5 years.



Application domain

- Meeting room
- School
- Office
- Medical areas



36 W

3400
lm

UGR
<19

IRC
>80

IP20

IP40
front

4000K



FILE UPDATED ON 13/02/2023

Electric data

Total power (W)	36
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
UGR	<19
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3400lm (4000K)
ULOR	-



FILE UPDATED ON 13/02/2023



Technical data

Dimensions (mm)	675 x 675 x 10
Recessed diameter (mm)	Min. : 670 Max. : 670
Weight (kg)	2.58
Recessed depth under BA13 (mm)	20
Cable length	-
Product color	White
IK Code	IK07
Incandescent wire test	650°C
IP Code	IP20 - IP40 front
Use temperature range	-20... +45°
Body material	Aluminium - PC
Diffuser material	PC
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	90°
Tiltable	No
Connection type	Connecteur rapide avec repiquage



FILE UPDATED ON 13/02/2023

