

TF104-ETANCHE TECH 150-43W-IP65-OPAL-3000K-850°

BL11586503

INDOOR > Triproof

Led waterproof strip, removable plate, 5-year warranty, Osram power supply, tool-free quick connector, through and 850°.



Application domain

- Industrial facilities
- Parkings lots and underground passages
- Garages
- Production areas, assembly plant
- Storage



FILE UPDATED ON 14/03/2023

Electric data

| | |
|-----------------------|-------|
| Total power (W) | 43 |
| Rated voltage (V) | 230V |
| Distorsion harmonique | <17% |
| Power factor | >0.95 |
| Network frequencies | 50Hz |
| Electric class | I |
| Dimmable | No |

Power supply data

| | |
|------------------------------------|----|
| Max. lamp per B10A circuit breaker | 12 |
| Max. lamp per B16A circuit breaker | 18 |
| Max. lamp per C16A circuit breaker | 25 |

Photometric data

| | |
|----------------------------|----------------|
| Color temperatures | 3000K |
| Light source type | SMD |
| Including the light source | Yes |
| SDCM | SDCM>4 |
| IRC | >80 |
| Safety group (EN62778) | RG1 |
| Luminous flux (lm) | 6000lm (3000K) |
| ULOR | - |



FILE UPDATED ON 14/03/2023



Technical data

| | |
|--------------------------------|----------------|
| Dimensions (mm) | 1520 x 85 x 80 |
| Weight (kg) | 1.82 |
| Recessed depth under BA13 (mm) | - |
| Cable length | - |
| Product color | Grey |
| IK Code | IK10 |
| Incandescent wire test | 850°C |
| IP Code | IP66 |
| Use temperature range | -20... +45° |
| Body material | PC |
| Diffuser material | PC |
| Driver included | Yes |

Liefe time

| | |
|-----------|----------|
| L80 à 25° | 50 000 h |
|-----------|----------|

Supplementary data

| | |
|-------------------|----------------------------------|
| Warranty period | 5 years |
| Light beam spread | 115° |
| Tiltable | No |
| Connection type | Connecteur rapide avec repiquage |



FILE UPDATED ON 14/03/2023





FILE UPDATED ON 14/03/2023