

LED PANEL

TF012-PANEL ECO UGR19-600x600-36W-3480lm-cadre WHITE-3000K

BL04452006

INDOOR > Office Recessed Fixture

Extra flat edge led panel.

Application domain

- Meeting room
- Office



36 W

3380
lm

UGR
<19*

IRC
>80

IP20

3000K



Electric data

Total power (W)	36
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	3000K
UGR	<19*
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3380lm (3000K)
ULOR	-

Technical data

Dimensions (mm)	595 x 595 x 8
Weight (kg)	2.94
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK07
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PS
Driver included	Yes
Recoverable	Insulation material except driver

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none">• BL08000013 - TF066-Protrusion frame 600x600• BL08000002 - TF018 Mechanically welded projection frame• BL08000006 - SUSPENSION KIT 600x600 tile• PL09302003 - DALI PUSH DIM POWER SUPPLY• BL08000009 - INTEGRATION FRAME 600x600