

EYE

EYE-ENC-MURAL-3W-4000K-IP20

BL16032002

INDOOR > Downlights (until 95 mm)

Eye LED module for recessing into walls indoors. Allows you to mark out and highlight interior or sheltered passageways: stairs, corridors. Finishing accessory to be ordered separately, round or square, white or black.



Application domain

- House Corridor
- Circulations areas
- Stairs



3 W

68 lm

IRC
>90IP54
facade

4000K



Electric data

Total power (W)	3
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

Photometric data

Color temperatures	4000K
Light source type	COB
Including the light source	Yes
SDCM	SDCM>4
IRC	>90
Safety group (EN62778)	RG0
Luminous flux (lm)	68lm (4000K)
ULOR	-

Technical data

Diameter (mm)	50
Height (mm)	35
Recessed diameter (mm)	Min. : 43 Max. : 46
Weight (kg)	0.1
Recessed depth under BA13 (mm)	30
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP54 facade
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Light beam spread	60°
-------------------	-----

Tiltable	No
----------	----

Connection type	Fil à connecter
-----------------	-----------------

Linked products

- BL16000001 - EYE-ACC-ROUND-WHITE
- BL16000002 - EYE-ACC-ROUND BLACK
- BL16000003 - EYE-ACC-SQUARE-WHITE
- BL16000004 - EYE-ACC-SQUARE-BLACK

Accessories

