

SQUARE

TF155-SQUARE LIGHT-300X300-15W-2CCT-DALI-BLACK

BL02152001

INDOOR > Surface mounted and suspended fixtures

To be surface-mounted, ideal for architectural projects, corridors with concrete ceiling, reception hall. This luminaire allows a very homogeneous light distribution while being aesthetic. Dimmable in Dali or push dim



Application domain

- Residential indoor
- Meeting room
- School
- Office
- Kitchen
- Home Office
- Circulations areas
- Entrance Halls



15 W

1500
lm

UGR
<19

IRC
>80

IP20

2 CCT

3000K / 4000K



Electric data

Total power (W)	15
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	II
Dimmable	Dali , push dim

Photometric data

Color temperatures	3000K / 4000K
UGR	<19
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1500lm (3000K)
ULOR	-

Technical data

Dimensions (mm)	300 x 300 x 80
Weight (kg)	2.66
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Black
IK Code	IK04
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	-
Driver included	Yes

Liefe time

L90 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	90°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none">• BL02000001 - MOON SQUARE BLACK SUSP KIT