

LED STRIP

LEDSTRIP PRO 5M-14,4W/M-IP20-2700K

BL21152014

[LED STRIP](#) > LED Strip

LED strip with a flux greater than 1200lm/m. Ideal for direct or indirect functional lighting. Cuttable every 3.3cm. Power cables at both ends. 3M adhesive on the back of the tape for easy installation.



Application domain

- Residential indoor
- Meeting room
- Office
- Kitchen
- Bedroom
- Home Office
- House Corridor
- Backlight
- Home Cellar, House Technical Room
- Circulations areas
- Stairs
- Entrance Halls
- Shop



FILE UPDATED ON 06/10/2022

Electric data

Total power (W)	14.4
Rated voltage (V)	24Vdc
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	0Hz
Electric class	III
Dimmable	Triac , Dali , 1-10V

Photometric data

Color temperatures	2700K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>3
IRC	>90
Safety group (EN62778)	RG1
Luminous flux (lm)	1267lm (2700K)
ULOR	-



FILE UPDATED ON 06/10/2022



Technical data

Weight (kg)	0.04
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK02
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-25... +45°
Body material	-
Diffuser material	-
Driver included	No

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data


Warranty period	5 years
Light beam spread	120°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none">• BL21000013 - TAPE ACC JUMPER 8MM IP20• BL21000011 - TAPE ACC CONNECTOR 8MM IP20• BL21000012 - TAPE ACC STARTER 8MM IP20



FILE UPDATED ON 06/10/2022



Plan



FILE UPDATED ON 06/10/2022

