

LED DOWNLIGHT

CAMUS PRO 20W-IP44-3000K-WHITE

TR02124413B

INDOOR > Downlight (100 to 240 mm)

Round white aluminum downlight. Very thin and with wide light distribution, it is ideal for tertiary applications. Dali Push-Dim option with suitable driver



Application domain

- Circulations areas
- Cloakrooms
- Shop



Electric data

Total power (W)	20
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	III
Dimmable	No

Photometric data

Color temperatures	3000K
UGR	<22
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1550lm (3000K)
ULOR	-

Technical data

Diameter (mm)	220
Height (mm)	13
Recessed diameter (mm)	Min. : 200 Max. : 210
Weight (kg)	0.52
Recessed depth under BA13 (mm)	30
Cable length	20 cm
Product color	White
IK Code	IK07
Incandescent wire test	650°C
IP Code	IP44 facade
Use temperature range	-20... +40°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none">PL09002001B - DALI PUSH POWER SUPPLY Camus

Other

