

CONSTRUCTION SPOTLIGHT

FLOODLIGHT CHANTIER 50W-IP65-6000K

PL10506510

WORKSITE > Floodlight

Site projector to accompany your work. Compact and resistant, it is supplied with a 3m power cable. 2 possible lighting modes: 50% and 100%. Site projector to accompany your work. Compact and resistant, it is supplied with a 3m power cable. 2 possible lighting modes: 50% and 100%.



Application domain

- Garages
- Production areas, assembly plant



Electric data

Total power (W)	50
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	I
Dimmable	No



FILE UPDATED ON 09/01/2023

Photometric data

Color temperatures	6000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>6
IRC	>70
Safety group (EN62778)	RG1
Luminous flux (lm)	5000lm (6000K)
ULOR	-

Technical data

Dimensions (mm)	32 x 200 x 180
Weight (kg)	1.06
Recessed depth under BA13 (mm)	-
Cable length	300 cm
Product color	Black
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-20... +40°
Body material	PC
Diffuser material	Verre trempé
Driver included	Yes



FILE UPDATED ON 09/01/2023



Liefe time

L70 à 25°	30 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	120°
Tiltable	No
Connection type	male FR plug
Linked products	<ul style="list-style-type: none">• PL10506511 - TRIPOD FOR CONSTRUCTION PROJ.

Other



FILE UPDATED ON 09/01/2023