

LED CEILING LIGHT

BARI DOWN SAILLIE-15/20/25W-3CCT-GRIS

PL12155402

INDOOR > Surface mounted and suspended fixtures

OUTDOOR > Ceiling Lights

Surface-mounted IP54 luminaire in aluminium, 3 powers 15W, 20W or 25W with the same product and 3 color temperatures (9 products in 1!). Ideal on hard ceiling (exterior awnings, interior concrete slab, etc.)



Application domain

- Circulations areas
- Outdoor Circulations
- Outdoor lighting



Electric data

Total power (W)	15 / 20 / 25
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 5700K
UGR	<19
Light source type	-
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	2650lm (4000K)
ULOR	-

Technical data

Diameter (mm)	213
Height (mm)	129
Recessed diameter (mm)	-
Weight (kg)	0.84
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Dark gray
IK Code	IK08
Incandescent wire test	850°C
IP Code	IP54
Use temperature range	-25... +40°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	90°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none">PL12155401 - BARI WHITE

