

PROJECTOR HOOK

RAFALE PATERE-15W-3CCT-WHITE-DIM

TR05152003

INDOOR > Surface mounted and suspended fixtures**INDOOR** > Wall light

LED spotlight on aluminum bracket with color temperature change.

**Application domain**

- Residential indoor
- Kitchen
- Bedroom
- House Corridor



15 W

1350
lmIRC
>80

IP20

3 CCT

3000K / 4000K
5700K

F

Electric data

| | |
|-----------------------|-------|
| Total power (W) | 15 |
| Rated voltage (V) | 230V |
| Distorsion harmonique | - |
| Power factor | >0.9 |
| Network frequencies | 50Hz |
| Electric class | I |
| Dimmable | Triac |

Photometric data

| | |
|----------------------------|-----------------------|
| Color temperatures | 3000K / 4000K / 5700K |
| Light source type | - |
| Including the light source | Yes |
| SDCM | SDCM>4 |
| IRC | >80 |
| Safety group (EN62778) | RG1 |
| Luminous flux (lm) | 1350lm (4000K) |
| ULOR | - |

Technical data

| | |
|--------------------------------|---------------|
| Dimensions (mm) | 156 x 70 x 70 |
| Weight (kg) | 0.66 |
| Recessed depth under BA13 (mm) | - |
| Cable length | 5 cm |
| Product color | White |
| IK Code | IK06 |
| Incandescent wire test | 650°C |
| IP Code | IP20 |
| Use temperature range | -20... +45° |
| Body material | Aluminium |
| Diffuser material | - |
| Driver included | Yes |
| Recoverable | Non concerné |

Liefe time

| | |
|-----------|----------|
| L70 à 25° | 50 000 h |
|-----------|----------|

Supplementary data

| | |
|-------------------|--|
| Warranty period | 3 years |
| Light beam spread | 38° |
| Tiltable | Yes (340°) |
| Connection type | Fil à connecter |
| Linked products | <ul style="list-style-type: none">TR07150002 - BURST CCT WHITE SHUTTER 15W |

Atmosphere



Other

