

WATERPROOF ECO

TF112-ETANCHE ECOPLUS -150-50W-4000K NON TRAV

BL11606502

INDOOR > Triproof

Non-through professional waterproof, ideal for technical rooms and workshops. Phillips driver.

Application domain

- Industrial facilities
- Parkings lots and underground passages
- Garages
- Production areas, assembly plant



50 W

5450
lmIRC
>80

IP65

4000K

E

Electric data

Total power (W)	50
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	5450lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	1585 x 60 x 60
Weight (kg)	1.24
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Grey
IK Code	IK08
Incandescent wire test	850°C
IP Code	IP65
Use temperature range	-20... +45°
Body material	PC
Diffuser material	PC
Driver included	Yes

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	120°
Tiltable	No
Connection type	fast connector