

LED PANEL

BOARD ASY-1200x300-4K

BL04362008

INDOOR > Office Recessed Fixture

Asymmetric recessed which allows the flow to be directed towards a wall or a painting. Ideal for classes, training centers etc...



Application domain

- Meeting room
- School



Electric data

Total power (W)	36
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
UGR	<19
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	4320lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	1195 x 295 x 22
Weight (kg)	2.86
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Iron
Diffuser material	-
Driver included	Yes
Recoverable	Isolant rouleau

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	60° X 95°
Tiltable	No
Connection type	fast connector

Other

