

LED PANEL

# TF065-PANEL EDGE PRO 1200x300-36W-4000k-UGR19-PRISMATIQUE

BL04452011

**INDOOR** > Office Recessed Fixture

300x1200 "edge" led panel with micro prismatic diffuser. UGR<19, ideal for installations in schools and tertiary environments.



## Application domain

- Meeting room
- School
- Office
- Medical areas



36 W

3600  
lm

UGR  
<19

IRC  
>85

IP20

IP40  
front

4000K



## Electric data

Total power (W)	36
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	4000K
UGR	<19
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>85
Safety group (EN62778)	RG0
Luminous flux (lm)	3600lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	1200 x 300 x 8
Weight (kg)	2.3
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK07
Incandescent wire test	650°C
IP Code	IP20 - IP40 front
Use temperature range	-20... +45°
Body material	-
Diffuser material	-
Driver included	Yes
Recoverable	Non recouvrable

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	90°
Tiltable	No
Connection type	Connecteur rapide avec repiquage
Linked products	<ul style="list-style-type: none"><li>• BL08000014 - 1200x300 projection frame KIT</li><li>• BL08000015 - Pendant kit 300x1200</li><li>• PL09302003 - DALI PUSH DIM POWER SUPPLY</li></ul>

